

Product Information



The Log Home Care and Maintenance Authority

Company Stores

Washington/Western Division

1-800-548-1231

Tennessee/Eastern Division

1-800-548-3554

Sevierville, TN

1-888-441-1116

Minnesota Branch

1-877-244-6548

Colorado Branch

1-800-433-8781

Montana Branch

1-800-479-7090

Stocking Distributors

Canadian Log Home Supply, Ontario

1-800-746-7773

Hess Log Home Supply, PA

1-800-257-4864

Log Home Center & Supply, IN

1-800-773-6223

Steels Industrial Products, Ltd., B.C.

(250) 374-3151

Timeless Wood Care Products, MI

1-800-564-2987

E-Wood™

Wood Epoxy for the Replacement of Damaged Wood for Interior and Exterior Use

Moldable * Carvable * Sandable

E-Wood will form a permanent bond to most rigid surfaces. Porous surfaces should first be coated with M-Balm. Use E-Wood to replace missing sections of windowsills, frames, furniture, or any wood structure. Use it to add new sections to already completed structures.

Directions:



With disposable gloves on both hands, knead together one part of E-Wood Epoxy (Part A) with one part E-Wood Hardener (Part B) by volume. Mix no more than can be applied within 15 minutes.

Application:

Apply over wood that has been treated and sealed with M-Balm. Mold to a rough finished shape.

Technique:

When cured, E-Wood can be sawed, nailed, carved, machined and sanded. E-Wood can tinted or painted.

Cleanup:

Uncured mixed E-Wood (**Part A and Part B**) may be cleaned up with white vinegar then flushed with water.

Shelf Life/Application Temperature:

E-Wood has a shelf life of 1 year. Application temperature is between 40° to 90°. Do not freeze!

Drying Time:

12 to 24 hours. E-Wood cures slower in low temperatures. (Never change mixing ratio to compensate for temperature.)

Color:

Wood tone.

Packaging:

E-Wood is available in 1-quart box and 2-gallon containers.

Surface Preparation:

Apply E-Wood on clean and dry surface that was restored with M-Balm.

Safety:

Always wear protective disposable gloves when using this product. Avoid skin contact. Skin sensitization may result from prolonged and repeated contact. If use causes soreness, redness, blistering, or other symptoms of irritation, stop use and see a physician immediately. Use with adequate ventilation. If eye contact occurs, flush with large quantities of water and contact a physician immediately. Do not use around open flame. If **Part A** is swallowed, induce vomiting. If **Part B** is swallowed, **Do Not** induce vomiting. **Keep out of reach of children.**

visit us
online
www.permachink.com