

# Product Information



## M-Balm™

### Wood Epoxy for Consolidation of Rotted Wood for Interior and Exterior Use

**Solvent-Free \* Reinforces \* Waterproof**

Penetrates deeply into deteriorated and rotted wood, creating a strong, solid base for restoration. After application, a patch may be built up with E-Wood, which can be finished in a normal manner. Use for repair of rotted and deteriorated, dried out or spongy wood. Excellent for both interior and exterior use. M-Balm penetrates deep into the wood, hardening into a strong, water resistant mass.

#### Directions:



Mix two parts of M-Balm Epoxy (Part A) with one part of M-Balm Hardener (Part B) by volume. Mix no more that can be applied within 30 minutes. For easy measurement, use mixing/applicator squeeze bottle.

#### Application:

Apply to affected area with mixing/applicator squeeze bottle, syringe, brush or roller. The wood must be very dry (15% moisture content or less). Repeat if necessary.

#### Technique:

In extreme cases of deep rot, drill a series of holes into the decayed area and pour liberally into the affected area. Allow time for M-Balm to soak well into the area. Repeat if necessary.

#### Cleanup:

Uncured mixed M-Balm (Part A and Part B) may be cleaned up with white vinegar then flushed with water.

#### Coverage:

Depends on porosity of wood.

#### Packaging:

M-Balm is available in 24-oz. bottles and 1.5-gallon containers.

#### Drying Time:

12 to 24 hours. M-Balm cures slower in low temperatures. (Never change mixing rates to compensate for temperature.)

#### Shelf Life/Application Temperature:

M-Balm has a shelf life of 1 year. Application temperature is between 40° to 90°. Do not freeze!

#### Safety:

**Always wear protective disposable gloves when using this product.** Avoid skin contact. Skin sensitization may result from prolonged and repeated contact. If use causes soreness, redness, blistering, or other symptoms of irritation, stop use and see a physician immediately. Use with adequate ventilation. If eye contact occurs, flush with large quantities of water and contact a physician immediately. Do not use around open flame. If **Part A** is swallowed, induce vomiting. If **Part B** is swallowed, **Do Not** induce vomiting. **Keep out of reach of children.**

The Log Home Care and  
Maintenance Authority

#### Company Stores

Washington/Western  
Division

1-800-548-1231

Tennessee/Eastern  
Division

1-800-548-3554

Sevierville, TN

1-888-441-1116

Minnesota Branch

1-877-244-6548

Colorado Branch

1-800-433-8781

Montana Branch

1-800-479-7090

#### Stocking Distributors

Canadian Log Home  
Supply, Ontario

1-800-746-7773

Hess Log Home Supply,  
PA

1-800-257-4864

Log Home Center &  
Supply, IN

1-800-773-6223

Steels Industrial  
Products, Ltd., B.C.

(250) 374-3151

Timeless Wood Care  
Products, MI

1-800-564-2987

visit us  
online  
[www.permachink.com](http://www.permachink.com)