

Directions for Use:

Proper surface preparation requires clean, dry surfaces, free from dirt, sawdust, loose particles of plaster or cement.

- For joints between deep foam pieces over 1/8 inch wide use backer rod to limit joint depth.
- Apply Stucco-Tex to grout void as evenly as possible.
- Apply Stucco-Tex™ to void, spray lightly with water as a tooling aid, trowel with thin flexible jointing tool.
- Trowel within 5 to 10 minutes as product will skin over quicker in hot weather.
- Apply at temperatures above 40° F. and protect from rain, freezing temperatures or moisture for a minimum of 8 hours.
- This product should not be used for structural repairs. Never apply as a coating or skim coat.
- Clean tools with soap and water as soon as possible after installation. Any excess materials should be cleaned off immediately with water.
- Stucco-Tex™ is freeze/thaw stable.

Manufactured by:



1-800-548-3554
www.permachink.com



MADE IN USA



1-800-305-1045
www.stucoflex.com

Instrucciones Para de Uso:

Preparación apropiado de la superficie requiere que sea limpia y seca, libres de suciedad, polvo, partículas sueltas de yeso o cemento.

Aplicar Estuco-Tex™ al vacío, rocíe ligeramente con agua como herramientas de ayuda, paleta con la herramienta de articulación.

- Llana dentro de 5 a 10 minutos como producto será descremada sobre más rápido en climas cálidos.
- Aplica a temperaturas superiores a F. 40° y proteger de la lluvia, congelación temperaturas o humedad durante un mínimo de 8 horas.
- Este producto no debe ser utilizado para reparaciones estructurales. Nunca aplique como revestimiento o capa ligera.
- Limpia los herramientas con jabón y agua tan pronto como sea posible después de la instalación. Cualquier exceso de materiales deben ser limpiado inmediatamente con agua.
- Estuco-Tex™ es congelar/descongelar estable.

Professional Grade Textured Elastomeric Sealant

STUCCO-TEX™

Profesional Grado Textura Sellante Elastomérico

FOR INTERIOR AND EXTERIOR



FLEXIBLE GROUT



STRETCHABLE SEALANT

AVAILABLE IN TEXTURED OR SMOOTH FINISH

**FOR USE
ON ANY
SURFACE
REQUIRING
A FLEXIBLE
SEAL**

- Stucco
- Masonry
- Brick
- Concrete
- Natural and Manufactured Stone
- Hardie-Plank™
- Metal
- Tile
- Wood

1605 Prosser Road, Knoxville, TN 37914

1-800-548-3554



Stucco-Tex™ expands and contracts with surface movement to help prevent cracks from reappearing.

- **Packaging:** 30 oz. plastic tubes.
- **Application Temperature Range, °F:** 40-90
- **Application Method:** Caulk Gun.
- **Coverage Rates, Linear ft. per 30 oz. tube (3/8" thick):**
1/4" bead size = 96', 1/2" bead size = 48'
- **Toxicity:** Non toxic.
- **Shelf Life:** 3 Years.
- **Drying Times:** 20 min. - 2 hr. (skin over) , 3-8 weeks (cure time)
Depends on temperature and humidity.
- **Clean-Up:** Soap and water.
- **Elongation, %:** 300 - 500
- **Freeze-Thaw:** Passes 5 cycles, (ASTM C-731)
- **Extrusion Rate, g/min:** 1400, (ASTM C-1183)
- **Density, lb./gal.:** 9.80 - 10.20



COLORS:

Stucco-Tex™ is available White and Mortar Match. Most foam and stucco applications can be painted. Other colors available by request.

www.permachink.com



1-800-548-3554



Cultured Stone without Stucco-Tex™



Cultured Stone with Stucco-Tex™

ESTUCO-TEX™

Estuco-Tex™ es un sellador flexible mortero de alta ejecución diseñado para hacer puente sobre grietas y proporcionar una transición decorativa para varios tipos de materiales de alta grado.

Estuco-Tex™ se expande y contrae con movimientos de la superficie para ayudar a evitar que vuelva a aparecer grietas. Puede ser utilizado en madera, estuco, mampostería, ladrillo, hormigón, Hardie-Plank™, piedra natural y manufacturada y metal. Prácticamente cualquier superficie que requieren un sello flexible.

Estuco-Tex™ se puede pintar con pinturas de látex para emparejar colores existentes o mejorar el diseño exterior (permite un mínimo de 24 horas antes de pintar).



www.stucoflex.com

1-800-305-1045

STUCCO-TEX™

Stucco-Tex™ is a high performance trowelable flexible sealant designed to bridge cracks and provide a decorative transition for various types of above grade materials.



Stucco-Tex™ can be painted with Latex paints to match existing colors or enhance exterior design (Allow a minimum of 24 hours prior to painting).

1-800-305-1045