

TECHNICAL TIP

RESOURCES ON HOW-TO'S, PRODUCT INFORMATION, AND EXPERT LOG & TIMBER HOME CARE

Bulk Loading Guns

The first question about bulk loading guns is whether they are worth buying. At current retail price levels (2022), comparing the retail cost of Perma-Chink® in pails to 30 oz tubes; the price of two pails is \$493.96 while the price of an equivalent amount of Perma-Chink in 30 oz tubes is \$748.80. Rather than buying four cases of 30 oz tubes you can purchase two pails of Perma-Chink and an Albion Bulk Loading Gun and a Follow Plate for \$135.54 and still have \$119.30 leftover. Plus, you will have a great tool for future use. In the case of EnergySeal®, the savings are even greater. Two pails of EnergySeal plus the Bulk Loading Gun and Follow Plate ends up being \$179.08 less expensive than four cases of 30 oz tubes.

So now that we know that bulk loading guns can save you money, how easy are they to use? First, do not try to save more money by not buying the Follow Plate. The Follow Plate is an integral part of the Bulk Loading Gun system and trying to load a gun without it can be a very frustrating and messy experience.

The procedure for loading and using an Albion Bulk Loading Gun step by step are:

Step 1

Remove the lid and the plastic liner from the pail. Put them aside and try to keep them clean in case you need to reseal the pail later.

Step 2

Place the follow plate on top of the product in the pail, making sure that there is a good seal between the wall of the pail and flexible edges of the Follow Plate.





Contact Us: 1-800-548-3554



TECHNICAL TIP

RESOURCES ON HOW-TO'S, PRODUCT INFORMATION, AND EXPERT LOG & TIMBER HOME CARE

Step 3

Remove the cap and cone tip from the end of the Albion Gun barrel and ensure that the rod and plunger are fully forward. Push the end of the barrel onto the lip surrounding the hole in the middle of the Follow Plate.

Make sure the gun is perpendicular to the plate and there is a tight seal between the barrel and O-ring. If the barrel is tilted, air will be sucked into the gun during the loading process.

Step 4

Depress the rod release plate and draw back the rod with a smooth, even pull. Make sure the barrel stays flush with the plate and do not tilt the gun as you pull the rod back.

Step 5

Once the rod is fully extended and the barrel is full of product, give the trigger one squeeze, then disengage the barrel from the Follow Plate with a twisting motion.

Step 6

Attach the end cap and cone tip to the end of the barrel. Make sure the tip of the cone is cut to the diameter of the bead you want to apply.









Contact Us: 1-800-548-3554



TECHNICAL TIP

RESOURCES ON HOW-TO'S, PRODUCT INFORMATION, AND EXPERT LOG & TIMBER HOME CARE

Step 7

Apply sealant using the same technique as you wood use with a standard caulk tube and ratchet gun.

Step 8

To remove the Follow Plate from an empty or partially full container, insert the handle rod into the open nut on the surface of the plate and pull it out.

Step 9

Replace plastic liner over the surface of the sealant.

Step 10

Replace the lid. Make sure that it is sealed tight on the pail.









Contact Us: 1-800-548-3554